

REF	DESIGNATION	DR60	DR90	DR120	DR150	DR240	DR300	DR150w	DR240w	DR300w	DR480w	DR600w
T19-A	Pole Ø19 mm 554 mm long	15										
T19-B	Pole Ø19 mm 726 mm long				30		72	14		50		
T19-C	Pole Ø19 mm 826 mm long	8	19					8				
T19-D	Pole Ø19 mm 975 mm long		4	8		16		8	12		26	117
T19-E	Pole Ø19 mm 1153 mm long			15	8	36	18		25	12	44	
C19-Y	Corner Ø19 mm 3 axes Y shape	8	8	8	8	8	8	8	8	8	8	8
C19-K	Corner Ø19 mm 4 axes K shape					8	8		4	4	16	28
C19-L	Link Ø19 mm Straight Joint	4	4	4	19	8	45	11	6	31	13	20
C19-XL	Link Ø19 mm Straight Joint XL					2	2				6	20
C19-H	Handling Ø19 mm 1 axe I shape	6	6	6	6	16	16	6	8	8	20	28
C19-SB	Space Booster Ø19 mm 2 axes Y shape	4	4	4	4	12	12	4	8	8		
C19-RF	Rubber Feet Ø19 mm 1 axe I shape						2				2	4
C19-RG	10x Link Ring O shape					1	1				2	4